EXECUTIVE ORDER U-R-025-0669

New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2016	GKBXL.276KCB	0.277	Diesel	3000				
	FEATURES & EMISSION (		TYPICAL EQUIPMENT APPLICATION					
	Indirect Diesel Inje	ction	Generator Set and Other Industrial Equipment					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			ŀ	EXHAUST (g/kw-l	•	OPACITY (%)			
POWER	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
kW < 8	Tier 4 Final	STD	N/A	N/A	7.5	8.0	0.40	N/A	N/A	N/A
		CERT	-		6.5	3.9	0.30			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

E0# U-K-0>5-0669

**Engine Model Summary Form** 

KUBOTA Corporation

Manufacturer:

Date: 10/30/2015

9. Emission Control 8.Fuel Rate: 7.Fuel Rate: Attachment page 1 of 5. Fuel Rate: 6. Torque @ RPM 4.Fuel Rate: 3.BHP@RPM New Submission GKBXL.276KCB Nonroad CI EPA Engine Family: Mfr Family Name: Engine category: Process Code:

		condition make	7,340	r instantanta	140			T T	P283	7574	L/E/S	100	20.2	563.1	5,475	EST	
			AL PARTIE				Ngi.	1130 3.54		(S.E.) 14.5 13.5 13.5 13.5 14.5	(2) (5) (5)				2,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00		275
0				9,				蒙				在 数据	77.5				
193(										5.2	100	基		1125 351	87	131 X	
5 П Э	塗	_			\$=0. (2)			1					12	190	2 (2) (2)		7.33 5.47
SAI	EMPLE	EM, IFI	EM, IFI								100 m						1614 415
Per	Σ	MΞ	Σ					27/4 12/5	96.16)						200		1995) 1,505 68 5a
Device Per SAE J1930		-							4	200					A S		
Sevi Sevi								- 52		744. 748	15 S					<b>1</b>	\$2657 6843 2017
						-								- 1500 1000 1000 1000 1000 1000 1000 1000		1741 1741	
	Ø17				ga ,				3(5)			\$3	等 数型		泰沙		
	(well) Signer							25									
*	4.3						10-0	6.5			1	<b>康</b> 斯					
pea 3							:16.4 -			000					. 1984 5-34	- 1500 E	
(a)	1.9	1.9	1.0		9.55 V.S.		Ã	5.5	影		210		- 755	Acc.		200 A	
(lbs/hr)@peak torque												140	100 mg	25			<u> </u>
9								2.5	A 190		(A) (A) (A)			17.00 17.00 17.00			
															15.70 15.70	2605 2005	
츛							嶷						<b>海</b>			13.0 35	
mm/stroke@peak torque	翻	:		1.5						(25)			海 吸流	- 1969 2001			
ke(c	21.4	21.0	14.9	1.5				2.45°					100 mg/s		121.53   131.53	15	
stro	7	7						560	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			24 25	
mr/								3442 4521 1221					Tario Cario	50			
<u>_</u>														400. 400.	100 A		
<u> </u>	32	-								22 (13)				44.0			(6)
(SEA Gross)	8	11.0@1600	20.3@1200		18.0		250 f		(1) (1) (1) (2) (2) (2)	101		1 6.5		16章 3音:		14 S	DIST.
3) (S	316	2	12										1960 1980		1945		444
ž Š	9	0	36		8						stells 97		1700 1200 1800	17.5			150es
<u>S</u>	12	Ξ	20		¥7.			45.5 460.6			1						500
0	2007 N						ing.		100		1000						
유 _					1					120		1944 1944				4531 3434	
(lbs/hr) @ peak HP (for diesels only)							333			1469 1585				274 374		6.7	\$ 100 \$ 40 \$ 40 \$ 100 \$
pe els	3.2	-	4.					\$714				L N			13.6 47.68		
(a)	က	3.1			麔									100	11 PA		
s/hr for c									100								
9 5						-			2000 2000								
₫																CIPA	
mm/stroke @ peak HP (for diesel only)								200								340 234	
onl on																	88
e @	45.8	15.5	14.9										2499 2480			1 200	AATS AATS AATS
r die	a Mir.	_	W														12.7555 4.2.744 55.684
n/st (fo																7	
Ē			10.00														25
			魔											459			
<u>₹</u> (g)	8	18	2					美		21.0					200		
2 8	6.7@3600	6.0@3600	12								1		500 500 500				
	0	0	18		140				1000 1140								
SAE Gross)	9	6.0	5.5@1700					65	FIJ.		優						
		٠.						27. 17.	10.00	100			(4) 446	7.73 200			
<u> </u>	100				製製 機能		£.	(A) 編言								36%	
pol		سا				ľ			200 200 200 200 200 200 200 200 200 200		1.						
<u>≥</u>	၂	끳	묏		髓	١.			(6.2500)				75			1	
2.Engine Model	OC60-EF	OC60-EF	OC60-EF					1500 1500 1500	25-200 22-45 32-45	100			200	施			
Ξ'n	0	O	0						234 234 2414			3.6					
2.1											Abis Mari						
									惹								36
ğ		2	3		100			· 鐵路	194 74.8								
O	130	EF0	IE.					9/3 6/4/2		100 to 10	l Prije	-   漢					
jin(	69	OC60-EF02	-09					78 (S)			1 16						
1.Engine Code	OC60-EF01	8	OC60-EF03					929 341 933 3									(Fg.
<del></del>									2.56 27.1								
	L	<b>1</b>	1	l	L	<u></u>	استسا			ــــــــــــــــــــــــــــــــــــــ	ــــــــــــــــــــــــــــــــــــــ	.L	1		ــــــــــــــــــــــــــــــــــــــ	1	